OPTICAL DRIVE

GP08NU40

EXTERNAL DVD REWRITER

Ultra Portable
Super-Multi Drive

FEATURES

ULTRA PORTABLE EXTERNAL DRIVE
- CONNECTS VIA USB 2.0

MAX. 8X DVD±R WRITE SPEED

MAX. 24X CD WRITE SPEED

CD-R/RW, DVD-R/RW/RAM/ +R/+RW +/-R DL
READ AND WRITE COMPATIBLE

2MB BUFFER UNDER RUN
PREVENTIVE FUNCTION

WINDOWS 7 COMPATIBLE



BURN IN STYLE

The LG Super-Multi GP08NU40 DVD Rewriter goes outside the conventional box with clean and fluent lines resulting in an elegant union of form and function. Simply plug via USB and burn CDs at 24x and DVD±Rs at 8x speeds. Satisfy your CD and DVD burning needs all in an aesthetic package.

super multi blue

OPTICAL DRIVE

GP08NU40

EXTERNAL DVD REWRITER

LG Life's Good

THE SUPER MULTI ADVANTAGE

Triple Compatibility
LG SuperMulti DVD Rewriter – SuperMulti optical drives can read and write three types of DVD formats in one convenient package:

1. DVD+R
2. RW DVD-R
3. RW DVD-RAM

This gives you the option to choose the media best suited for each task.

TECHNICAL SPECIFICATIONS

TYPE	SUPER-MULTI PORTABLE SLIM DVD-REWRITER	
TRANSFER RATES-WRITE	DVD+R	2.4x CLV, 4x ZCLV, 8x CAV
	DVD+R DL	2,4x CLV, 4x ZCLV
	DVD+RW	2.4x CLV, 4x ZCLV, 6x ZCLV, 8x ZCLV
	DVD-R	2x CLV, 4x ZCLV, 8x CAV
	DVD-R DL	2.4x CLV, 4x ZCLV
	DVD-RW	2x CLV, 4x ZCLV, 6x ZCLV
	DVD-RAM	2x ZCLV, 3x ZCLV, 5x PCAV
	CD-R	10x CLV, 16x PCAV, 24x CAV
	CD-RW	Multi Speed: 4X CLV High Speed: 4X CLV, 10X CLV Ultra Speed: 10X CLV, 16X ZCLV Ultra Speed+: 10x CLV, 16x ZCLV
TRANSFER RATES-READ	DVD-ROM(SL/DL)	8x CAV
	DVD+R (SL/DL)	8x CAV / 6x CAV
	DVD+RW	8x CAV
	DVD-R (SL/DL)	8x CAV / 6x CAV
	DVD-RW	8x CAV
	DVD-Video (CSS title)	4x CAV
	DVD-RAM(Ver. 1.0/2.2)	5x PCAV / 2x CLV
	CD-ROM/R/RW	24x CAV
	CD-DA (DAE) (Digital Audio Play)	24x CAV
ACCESS TIME	DVD-ROM	135 ms (typ.)
	CD-ROM	135 ms (typ.)
SUSTAINED RATE	DVD-ROM	11.08Mbytes/s (8x) max
	CD-ROM	3,600 kB/s (24x) max
BURST TRANSFER RATE	External (Host)	480Mbit/s (USB2.0)
	Internal (Drive)	33.3Mbytes/smax. (UltraDMAMode2) 16.6Mbytes/smax. (DMAMWMode2) 16.6Mbytes/smax. (PIOMode 4)
BUFFER SIZE	2MB Under-run prevention function embedded	
HOST INTERFACE	External (Host)	USB2.0 (480Mbit/s)
	Internal (Drive)	ATAPI comliant (X3T9.2/791D and SFF-8090i Ver5.0 Rev1.5) SFF-8080 Rev1.2 ,MMC-4 (MMC Spec for CD-R/RW)
OPERATING SYSTEM	Windows 7, Windows Vista™, Windows XP, Windows, Mac OS X ver. 10.5.4 or higher	
SYSTEM REQUIREMENTS	CPU Pentium® III 1.0GHz or Higher (with USB 2.0) RAM256MB or Higher	
DIMENSIONS (W X H X D)	5.6" x 0.6" x 6.1" (141.1 x 14.8 x 156.2 mm)	
WEIGHT	0.9 lbs (411g)	

www.LGusa.com

LG Electronics U.S.A., Inc.
1000 Sylvan Avenue Englewood Cliffs, NJ 07632
Customer Service and Technical Support: (800) 243-0000

Dimensions and weights are approximate. Design, features and specifications subject to change without notice.